

TYPE APPROVAL CERTIFICATE

This is to certify:**That the Miscellaneous Fittings for Pressurised Equipment**with type designation(s)
LPG hose 659AA EN1762 Type D - M

Issued to

**Alfagomma Industrial S.p.A.
Industrial Hose Division - Alfagomma Group
Zona Industriale - 64100 Sant'Atto TE, Italy**is found to comply with
EN 1762:2018**Application :****Non-metallic flexible tube type LPG 659AA 25bar (LPG tube black with high tensile textile cords and antistatic wires) without couplings, according to EN1762:2018 - Size 13, 16, 19, 25, 32, 38 and 51**Issued at **Esbjerg** on **2018-11-06**for **DNV GL**This Certificate is valid until **2023-11-05**.DNV GL local station: **Milan Verification**Approval Engineer: **Gaetano Ricci****Pedersen, Lars Henning
Head of Section for Pipelines &
Equipment (O-ED-PIEQ)**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-030018-2**
Certificate No: **TAP00001KR**
Revision No: **1**

Product description

- LPG DELIVERY 25 bar (375 psi)
- BLACK NBR
- Reinforcement: HIGH TENSILE TEXTILE CORDS - ANTISTATIC WIRES
- Cover: BLACK CR - ABRASION, OZONE, HYDROCARBON AND FIRE - RESISTANT - PIN PRICKED

Application/Limitation

- LPG DELIVERY IN HEAVY DUTY REELING APPLICATIONS
- Size: 13, 16, 19, 25, 32, 38 and 51
- Max Working Pressure: 25 bar
- Temperature Range: -30 °C to +70 °C (-22 °F to +158 °F)
- Please consider that this certificate is not valid for products (materials, component or equipment) subjected to DNVGL classification.

Type Examination documentation

- Technical Data Sheet – LPG DELIVERY 25 bar (375 psi) – code: 659 AA
- *Test plan for components*
- *Test plan for hose*
- *Alfagomma Test Report No. 659AA1323 for hose type 659 AA 13 x 23*
- *Alfagomma Test Report No. 659AA1626 for hose type 659 AA 16 x 26*
- *Alfagomma Test Report No. 659AA2538 for hose type 659 AA 25 x 38*
- *Alfagomma Test Report No. 659AA5167 for hose type 659 AA 51 x 67*
- *Calibration certificates*
- *Gap Analysis requirements EN1762:2017 and EN1762:2018*

Tests carried out

According with EN1762:2017:

(Tests on components)

- Tensile strength (Table 3 – Item 1)
- Elongation at break (Table 3 – Item 2)
- Abrasion resistance (Table 3 – Item 3)
- Harness change after ageing in air (Table 3 – Item 4)
- Tensile strength change after ageing in air (Table 3 – Item 4)
- Elongation at break change after ageing in air (Table 3 – Item 4)
- Mass increase after ageing in n-pentane (Table 3 – Item 5.1)
- Hardness after ageing in n-pentane (Table 3 – Item 5.2)
- Mass reduction after ageing in n-pentane and drying in air (Table 3 – Item 5.2)
- Ozone resistance (Table 4 – Item 7)

(Tests on hoses)

- Tolerance on inside diameter (Table 1)
- Tolerance on outside diameter (Table 1)
- Minimum lining thickness (Par. 6.2)
- Minimum cover thickness (Par. 6.2)
- Concentricity (Par. 6.3)
- Proof pressure (Table 4 – Item 1)
- Change in length at proof pressure (Table 4 – Item 2)
- Change in twist at proof pressure (Table 4 – Item 3)
- Burst test (Table 4 – Item 5)
- Adhesion (Table 4 – Item 6)
- Low temperature flexibility (Table 4 – Item 8)
- Electrical resistance (Table 4 – Item 9)
- Flammability test (Table 4 – Item 10)
- Max deformation of external diameter at min bend radius (Table 4 – Item 11)

Job Id: **262.1-030018-2**
Certificate No: **TAP00001KR**
Revision No: **1**

Marking of product

Marking of products shall be as a minimum:

- (Brand Text) AG-ITALY-659 LPG DELIVERY + AG-25BAR (375PSI) LPG-EN1762:2018-TYPE D-M-
_____mm QQ/yy
- (Brand Type) ORANGE LETTERS + EMBOSSED

Certificate Retention Survey

For retention of the Type Approval/Examination, DNV GL Surveyor shall perform a survey every second year, to verify that the conditions for the type examination are complied with unless the hoses are regularly certified by DNV GL