

# TYPE APPROVAL CERTIFICATE

**This is to certify:**

**That the Flexible Hoses of Non-Metallic Material with Permanently Fitted Couplings**

with type designation(s)

**Flexor 1SN/1AT-HF (Dunlop Hiflex: Greenline plus 122), Flexor 2SN/2AT-HF (Dunlop Hiflex: Greenline plus 222), 1SN MINETUFF (Dunlop Hiflex: 1SN HI-TUFF), 2SN MINETUFF (Dunlop Hiflex: 2SN HI-TUFF)**

Issued to

**Alfagomma Hydraulic S.p.A.**  
**Castelnuovo Vomano, TE, Italy**

is found to comply with

**DNV GL rules for classification – Ships Pt.4 Ch.6 Piping systems**  
**DNVGL-OS-D101 – Marine and machinery systems and equipment, Edition January 2018**  
**DNV GL class programme DNVGL-CP-0183 – Type approval – Flexible hoses**

**Application :**

**Product(s) approved by this certificate is/are accepted for installation on vessels classed by DNV GL.**

Type:	Temperature range:	Max. working press.:	Sizes:
<b>Flexor 1SN/1AT-HF (Dunlop Hiflex: Greenline plus 122)</b>	<b>-40°C to +100°C</b>	<b>40 bar to 225 bar</b>	<b>DN6 to DN51</b>
<b>Flexor 2SN/2AT-HF (Dunlop Hiflex: Greenline plus 222)</b>	<b>-40°C to +100°C</b>	<b>80 bar to 400 bar</b>	<b>DN6 to DN51</b>
<b>1SN MINETUFF (Dunlop Hiflex: 1SN HI-TUFF)</b>	<b>-40°C to +100°C</b>	<b>40 bar to 225 bar</b>	<b>DN6 to DN51</b>
<b>2SN MINETUFF (Dunlop Hiflex: 2SN HI-TUFF)</b>	<b>-40°C to +100°C</b>	<b>80 bar to 400 bar</b>	<b>DN6 to DN51</b>

Issued at **Høvik** on **2020-01-31**

for **DNV GL**

This Certificate is valid until **2024-06-30**.

DNV GL local station: **Italy/Malta CMC**

Approval Engineer: **Adel Samiei**

**Zeinab Sharifi**  
**Head of Section**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.



Job Id: **262.1-010925-3**  
 Certificate No: **TAP000002W**  
 Revision No: **1**

## Product description

Four types of hose assemblies. Hoses and fittings are manufactured by ALFAGOMMA Hydraulic SPA.  
 Hoses:

- Flexor 1SN/1AT-HF (Dunlop Hiflex: Greenline Plus 122) & 1SN MINETUFF (Dunlop Hiflex: 1SN HI-TUFF), Designed according to EN853 / 1SN  
 Tube: Oil Resistant synthetic rubber  
 Reinforcement: One high tensile steel braid (1B)  
 Cover: Abrasion, Ozone and hydrocarbon resistant synthetic rubber
- Flexor 2SN/2AT-HF (Dunlop Hiflex: Greenline Plus 222) & 2SN MINETUFF (Dunlop Hiflex: 2SN HI-TUFF), Designed according to EN853 / 2SN  
 Tube: Oil Resistant synthetic rubber  
 Reinforcement: Two high tensile steel braids (2B)  
 Cover: Abrasion, Ozone and hydrocarbon resistant synthetic rubber

Couplings:

- Flexor 1SN/1AT-HF & 1SN MINETUFF (Dunlop Hiflex: Greenline Plus 122 & 1SN HI-TUFF)

Nominal size (DN / inch)		Carbon Steel 11SMnPb30 Stainless Steel AISI 316				AG Branding*
		Skive fittings 1SN/1AT-HF		No Skive fittings 1SN/1AT-HF		
		AG Branding	DH Branding	AG Branding	DH Branding	
6	¼	H1100204-04	D330000-04/0	H1200102-04	D110000-04/0	H1200AD1-04
8	5/16	H1100204-05	D330000-05/0	H1200202-05	D110000-05/0	H1200AD1-05
10	3/8	H1100204-06	D330000-06/0	H1200212-06	D110000-06/0	H1200AD1-06
12	½	H1100204-08	D330000-08/0	H1200212-08	D110000-08/0	H1200AD1-08
16	5/8	H1100204-10	D330000-10/0	H1200202-10	D110000-10/0	H1200AD1-10
19	¾	H1100204-12	D330000-12/0	H1200202-12	D110000-12/0	H1200AD1-12
25	1	H1100204-16	D330000-16/0	H1200202-16	D110000-16/0	H1200AD1-16
31	1 ¼	H1100104-20	H1100104-20	H1200102-20	D110000-20/0	H1200AD1-20
38	1 ½	H1100104-24	H1100104-24	H1200202-24	D110000-24/0	H1200AD1-24
51	2	H1100104-32	H1100104-32	H1200202-32	D110000-32/0	H1200AD1-32

- Flexor 2SN/2AT-HF & 2SN MINETUFF (Dunlop Hiflex: Greenline Plus 222 & 2SN HI-TUFF)

Nominal size (DN / inch)		Carbon Steel 11SMnPb30 Stainless Steel AISI 316				AG Branding*
		Skive fittings		No Skive fittings		
		AG Branding	DH Branding	AG Branding	DH Branding	
6	¼	H1100404-04 H3100404-04	D330000-04/0	H1200202-04	D220000-04/0	H1200AD2-04
8	5/16	H1100404-05 H3100404-05	D330000-05/0	H1200202-05	D220000-05/0	H1200AD2-05
10	3/8	H1100404-06 H3100404-06	D330000-06/0	H1200212-06	D220000-06/0	H1200AD2-06
12	½	H1100404-08 H3100404-08	D330000-08/0	H1200212-08	D220000-08/0	H1200AD2-08
16	5/8	H1100404-10 H3100404-10	D330000-10/0	H1200202-10	D220000-10/0	H1200AD2-10
19	¾	H1100404-12 H3100404-12	D330000-12/0	H1200202-12	D220000-12/0	H1200AD2-12
25	1	H1100404-16 H3100404-16	D330000-16/0	H1200202-16	D220000-16/0	H1200AD2-16
31	1 ¼	H1100404-20 H3100404-20	D330000-20/0	H1200202-20	D220000-20/0	H1200AD2-20
38	1 ½	H1100404-24 H3100404-24	D330000-24/0	H1200202-24	D220000-24/0	H1200AD2-24
51	2	H1100404-32 H3100404-32	D330000-32/0	H1200202-32	D220000-32/0	H1200AD2-32

\*) AD1 and AD2 coupling are the Alfagomma branding of D11 and D22 coupling branding Dunlop Hiflex

Job Id: **262.1-010925-3**  
Certificate No: **TAP000002W**  
Revision No: **1**

## Application/Limitation

This certificate is valid for the specific assembly of hose and coupling type as specified, assembled and delivered by the holder (named as manufacturer) of this certificate or below assembling locations:

- 1) Alfagomma Hydraulic S.P.A., Mangone, Italy
- 2) Dunlop Hiflex AB, Halmstad, Sweden
- 3) Dunlop Hiflex OY, Turku, Finland
- 4) Alfagomma hydraulic S.P.A, Bellusco, Italy excluding 2SC
- 5) Alfagomma Germany GmbH, Herne, Germany Except 1SN/2SN MINETUFF
- 6) Alfagomma Germany GmbH, Hamburg, Germany Except 1SN/2SN MINETUFF
- 7) Dunlop Hiflex AS, Oslo, Norway
- 8) Dunlop Hiflex AS, Ålesund, Norway
- 9) Dunlop Hiflex AS, Stavanger, Norway
- 10) Dunlop Hiflex AS, Bergen, Norway
- 11) Dunlop Hiflex AS, Kristiansand, Norway
- 12) Dunlop Hiflex AS, Esbjerg, Denmark
- 13) Dunlop Hiflex AS, Kolding, Denmark
- 14) Alfagomma UK Ltd, Hydock, UK
- 15) Alfagomma Korea Co, Ltd., Hwaseong-Si, Gyeonggi-do, Korea
- 16) Alfagomma (Ningbo) Co. Ltd, Ningbo, China Just 1SN/2SN MINETUFF

Hose assemblies are approved to use with:

- Petroleum based hydraulic fluids at temperatures ranging from -40 °C + 100 °C;
- Water based fluids at temperatures ranging from -40 °C to +70 °C;
- Water and Air at temperatures ranging from 0 °C to +70 °C.
- Fuel Oil
- CO2 systems at temperatures ranging from -60°C to 100°C(Just hose assemblies 1SN MINETUFF (Dunlop Hiflex:1SN H1-TUFF ) with AD1 couplings (or D11 Dunlop Hiflex branding) up to size 1" can be used in CO2 applications)

Maximum working pressure of each hose assemblies shall be as follows:

Nominal size (DN / inch)	1SN/1AT HF 1SN MINETUFF	2SN/2AT HF 2SN MINETUFF	
6	1/4	225 bar	400 bar
8	5/16	215 bar	350 bar
10	3/8	180 bar	330 bar
12	1/2	160 bar	275 bar
16	5/8	130 bar	250 bar
19	3/4	105 bar	215 bar
25	1	88 bar	165 bar
31	1 1/4	63 bar	125 bar
38	1 1/2	50 bar	90 bar
51	2	40 bar	80 bar

Flexible hoses are only to be used in short lengths where it is necessary due to vibrations or flexible mounting of the machinery. The hoses shall not replace/be used where permanent piping is possible/required.

The hose assemblies must only be fitted in places where they are always accessible. Flexible hoses of these types are not to be used on boiler fronts.

The hoses are to be mounted in accordance with the manufacturer's instructions.

Hose assemblies covered by this certificate shall not be used in system subject to pressure below atmospheric or vacuum condition.

The cover of hoses for gaseous applications shall be pin-pricked.

Job Id: **262.1-010925-3**  
Certificate No: **TAP000002W**  
Revision No: **1**

## Production testing

All hose assemblies delivered under the DNV GL type approval scheme shall be subject to a pressure test at 1.5 times the maximum working pressure and shall be delivered with the pressure test report with reference to this type approval certificate.

## Type Approval documentation

ALFAGOMMA technical datasheets no. 255 (FLEXOR 1SN/1AT-HF) and no. 257 (FLEXOR 2SN/2AT-HF) dated 2010-03-15

ALFAGOMMA technical datasheets no. 305 (1SN MINETUFF) and no. 307 (2SN MINETUFF) dated 2015-04-15

Burst test and change in length test reports numbers (stamped as witnessed by DNV/DNV GL):

- 33/2010, 34/2010, 15/2010 & 35/2010 dated 2010-12-16 (1SN/1AT HF - DN6, 10, 20 & 38)
- 09/2015, 10/2015, 11/2015 & 12/2015 dated 2015-07-20 (1SN/1AT HF with AD1 couplings DN6, 12, 25 & 51)
- 01/2015, 02/2015, 03/2015 & 04/2015 dated 2015-07-20 (1SN MINETUFF with AD1 couplings DN6, 12, 25 & 51)
- 13/2015, 14/2015, 15/2015 & 16/2015 dated 2015-07-20 (2SN/1AT HF with AD2 couplings DN6, 12, 25 & 51)
- 05/2015, 06/2015, 07/2015 & 08/2015 dated 2015-07-20 (2SN MINETUFF with AD2 couplings DN6, 12, 25 & 51)
- 38/2010, 36/2010, 16/2010 & 37/2010 dated 2010-12-16 (2SN/2AT - DN5, 10, 20 & 38)

Burst test reports (@-65°C) numbers (stamped as witnessed by DNV/DNV GL):

- 001/2014, 002/2014 & 003/2014 dated 2014-08-01 (1SN/1AT HF - DN6, 12 & 20)
- 17/2015, 18/2015 & 19/2015 dated 2015-07-21 (1SN MINETUFF - DN6, 12 & 20)

Fire test reports (done by LAPI) numbers:

- 1666.OIS0110/10 (1SN/1AT - DN6), 1667.OIS0110/10 (1SN/1AT - DN16) & 1668.OIS0110/10 (1SN/1AT - DN51) with H1100204 type fittings / dated 2010-11-26
- 1669.OIS0110/10 (2SN/2AT - DN6), 1670.OIS0110/10 (2SN/2AT - DN16) & 1671.OIS0110/10 (2SN/2AT - DN51) with H1100204 type fittings / dated 2010-11-26
- 767.OIS0110/15 (1SN MINETUFF - DN6), 768.OIS0110/15 (1SN MINETUFF - DN16) & 769.OIS0110/15 (1SN MINETUFF - DN51) with AD1 type fittings / dated 2015-06-01
- 770.OIS0110/15 (2SN MINETUFF - DN6), 771.OIS0110/15 (2SN MINETUFF - DN16) & 772.OIS0110/15 (2SN MINETUFF - DN51) with AD2 type fittings / dated 2015-06-01
- 279.OIS0110/18 (2SN - DN6), 280.OIS0110/18 (2SN - DN20) & 281.OIS0110/18 (2SN - DN51) with H3100404 & H32XXXXX couplings

Impulse test reports numbers:

- 074/09 (1SN - DN6), 094/10 (1SN-DN12), 090/09 (1SN - DN25), 080/09 (1SN -DN38), 128/10 (2SN - DN5), 120/09 (2SN - DN10), 106/09 (2SN - DN19) & 076/09 (2SN - DN38)
- 227/14, 232/14, 221/14 & 003/14 (1SN MINETUFF - DN6, 12, 25 & 51) with AD1 couplings
- 228/14, 223/14, 240/14 & 012/14 (2SN MINETUFF - DN6, 12, 25 & 51) with AD2 couplings

Change in length, dimensional check, abrasion resistance, cover adhesion test, oil resistance test, cold flexibility test, ozone resistance test reports numbers: 427-10, 428-10, 429-10, 430-10, 431-10, 432-10, 433-10, 434-10, 435-10, 436-10, 437-10, 438-10, 439-10, 440-10, 441-10, 442-10, 443-10, 444-10, 191-10 & 192-10, 01/2015, 02/2015, 03/2015, 04/2015, 05/2015, 06/2015, 07/2015, 08/2015, 09/2015, 10/2015, 11/2015, 12/2015, 13/2015, 14/2015, 15/2015 & 16/2015 dated 2015-07-04

Renewal Burst pressure test and change in length test reports numbers:

017,018,019,020,021,022,023,024,025,026,027,028,029,030,031,032,033,034,035,036,037,038,039,040,041,042,043,044,045,046,047,048,049,050,051,052,053,054,055,056,057,058,066,067,095,096,097,098,099,100,101,102,103,104,105,106,107,108,109,110

Endurance test reports 03677RP19 dated 2019-11-29 & 03789RP20 dated 2020-01-23

## Tests carried out

Change in length, dimensional check, abrasion resistance, cover adhesion est, oil resistance test, cold flexibility test, ozone resistance, fire test, burst pressure, impulse test.

Job Id: **262.1-010925-3**  
Certificate No: **TAP000002W**  
Revision No: **1**

### **Marking of product**

For traceability to this Type Approval, the products are at least to be marked with:

- hose manufacturer's name or trademark;
- date of manufacture (month/year);
- designation type reference;
- nominal diameter;
- pressure rating;
- temperature rating.

### **Periodical assessment**

For retention of the Type Approval, a DNV GL Surveyor shall perform periodical assessment after two years (+/- 90 days) and after 3.5 years (+/- 90 days) to verify that the conditions for the approval are complied with. Reference is made to DNVGL-CP-0338.