

TYPE APPROVAL CERTIFICATE No. **MAC260620CS**

This is to certify that the product identified below is in compliance with the regulations herewith specified.

Description Non metallic flexible hoses

Type 405 LE

455LE

ALFAGOMMA INDUSTRIAL S.P.A. A pplicant

VIA ATTILIO DI SANTE, SNC

64100 S. Atto (TE)

ITALY

Manufacturer ALFAGOMMA INDUSTRIAL S.P.A.

Place of manufacture VIA ATTILIO DI SANTE, SNC

64100 S. Atto (TE)

ITALY

Reference standards Part C, Chapter 1, Section 10 of RINA Rules

Issued in Genova on August 29, 2020. This Certificate is valid until August 28, 2025

RINA Services S.p.A. Marco Dardano

This certificate consists of this page and 1 enclosure.

This Certificate annuls and replaces the Certificate MAC361319CS/01 issued on 25/11/2019.

TYPE APPROVAL CERTIFICATE No. MAC260620CS Enclosure - No. 2 Pages 405 LE 455LE

Reference documents

Alfagomma technical data sheet 02/10/2019 and 29/06/2020.

Test Reports:

- ALFAGOMMA No. 405LE019-1/2/3 Burst Test;
- ALFAGOMMA No. 405LE032-1/2/3 Burst Test
- ALFAGOMMA No. 405LE038-1/2/3 Burst Test;
- ALFAGOMMA No. 455LE013-1/2/5 Burst Test;
- Cerisie No. 630-A/2019 D.M. 174 del 06/04/2004 455LE Di 13 mm;
- Cerisie No. 630-B/2019 D.M. 174 del 06/04/2004 405LE Di 19 mm;
- Cerisie No. 092-A/2020 D.M. 174 del 06/04/2004 405LE Di 25 mm;
- Cerisie No. 092-B/2020 D.M. 174 del 06/04/2004 405LE Di 32 mm;
- Cerisie No. 630-C/2019 D.M. 174 del 06/04/2004 405LE Di 38 mm;
- TIFQLAB No 1169/1 AISI 316 AISI 316L (insert 455LE Di 13 mm);
- TIFQLAB No 1252/1 AISI 316 AISI 316L (insert 455LE Di 13 mm);
- TIFQLAB No 1169/2 AISI 316 AISI 316L (insert 405LE Di 19 mm);
- TIFQLAB No 1252/2 AISI 316 AISI 316L (insert 405LE Di 19 mm);
- TIFQLAB No 1252/3 AISI 316 AISI 316L (insert 405LE Di 25 mm);
- TIFQLAB No 1252/4 AISI 316 AISI 316L (insert 405LE Di 25 mm);
- TIFQLAB No 1252/5 AISI 316 AISI 316L (insert 405LE Di 32 mm);
- TIFQLAB No 1252/6 AISI 316 AISI 316L (insert 405LE Di 32 mm);
- TIFQLAB No 1169/3 AISI 316 AISI 316L (insert 405LE Di 38 mm);
- TIFQLAB No 1252/7 AISI 316 AISI 316L (insert 405LE Di 38 mm).

Technical data [see next page]

RINA Services S.p.A. Via Corsica, 12 - 16128 Genova Tel +39 010 53851 Fax +39 010 5351000

Hose fitting combination

455 LE									
SIZE	ID			Famula	Incom				
	mm	in	Dash	Ferrule	Insert				
12,22	13 1/2" -08 H3200TXL-08000	112200TVI 000000	H32XXXXX-08XXXX						
13x23		1/2	-08	H32001XL-080000	I37XXXXX-A0013				

405 LE								
SIZE	ID			Ferrule	Insert			
	mm	in	Dash	rerruie	insert			
19x31	19	3/4"	-12	H3200TXL-120000	H32XXXXX-12XXXX			
					I37XXXXX-A00019			
25x37	25	1"	-16	H3200TX2-160000	137XXXXX-A00025			
					H32XXXXX-16XXXX			
32x42	32	1 1/4"	-20	H3200TX2-200000	H32XXXXX-20XXXX			
					137XXXXX-A00032			
38x50	38	1 1/2"	-24	H3200TX2-240000	H32XXXXX-24XXXX			
					137XXXXX-A00038			

Pressure rating: 10 bar

Fields of application

Fresh/Potable water in accordance to Italian D.M.174 dated 06/04/2004 (with Insert made of AISI 316 and AISI 316L).

Remarks

The installation on board is to be carried out by qualified personnel in accordance with the manufacturer's instructions.

The flexible hoses are to be installed in order to satisfy the requirements of para. 5.9.3 of Part C, Chapter 1, Section 10 of RINA Rules.

The acceptance of the a.m. products on board ship classed with RINA is subject to the satisfactory outcome of testing as per RINA Rules.

The product (hose and fittings) is to be marked, for traceability, with the following data: nominal diameter, design conditions, Manufacturer's name or trademark, designation type reference.

This Type Approval Certificate is valid for hoses connected to the machinery/system with flange and/or threaded connection (in accordance with limitation in Pt. C, Ch. 1, Sec. 10, Tab. 15 of RINARules) only. Other fitting defined as mechanical joints (Rina Rules Pt. C, Ch. 1, Sec. 10, Para. 2.4.5 Fig. 2), could be accepted upon satisfactory result of prototype tests performed on hose/fitting assemblies.

Genova 29/08/2020