



NIPPON KAIJI KYOKAI

TYPE APPROVAL CERTIFICATE

Certificate No. TA21512M

This is to certify that the undernoted product(s) has/have been approved in accordance with the requirements 12.1.6, Chapt.12, Part D of "Rules for the Survey and Construction of Steel Ships" and Chapt.2, Part 6 "Guidance for the Approval and Type Approval of Materials and Equipment for Marine Use".

This certificate is issued to

Manufacturer:

ALFA GOMMA S.p.A., Italy

Product description:

HYDRAULIC HOSE ASSEMBLY

Type designation(s):

Alfagomma / Dunlop Hiflex

Flexor 1SN HF / 122GP

Flexor 1SN MINETUFF / 1SN HI-TUFF

Flexor 2SN HF / 222GP

Flexor 2SN MINETUFF / 2SN HI-TUFF

Flexopak 2 / Super Slimline 241T&241G&241X Flexopak 2SC HF / Slimline Plus 221T&221G

Approval No.:

00FV402B

Valid until:

20 July 2025

This certificate is subject to the conditions specified in the attached sheet(s).

Issued at Tokyo on 6 October 2021

T. Shimada General Manager Machinery Department Particulars and conditions:

Particulars and conditions:								
Туре	DN		Max. Working Pressure	Design Temperature	Material of Hose			
	[inch]	[mm]	[bar]	(°C)				
Alfagomma Flexor 1SN HF / Dunlop Hiflex 122GP Alfagomma Flexor 1SN MINETUFF / Dunlop Hiflex 1SN HI-TUFF	1/4	6	225	-40~+100	Tube; Oil resistant Synthetic rubber Reinforcement; I wire braid Cover; Abrasion, Ozone and Hydrocarbon resistant synthetic rubber			
	5/16	8	215					
	3/8	10	180					
	1/2	12	160					
	5/8	16	130					
	3/4	19	105					
	1	25	88					
	1 1/4	32	63					
	1 ½	38	50					
	2	51	40					
Alfagomma Flexor 2SN HF / Dunlop Hiflex 222GP Alfagomma Flexor 2SN MINETUFF / Dunlop Hiflex 2SN HI-TUFF	1/4	6	400	-40~+100	Tube; Oil resistant Synthetic rubber Reinforcement; 2 wire braid Cover; Abrasion, Ozone and Hydrocarbon resistant synthetic rubber			
	5/16	8	350					
	3/8	10	330					
	1/2	12	275					
	5/8	16	250					
	3/4	19	215					
	1	25	165					
	1 1/4	32	125					
	1 ½	38	90					
	2	51	80					
3SPT/3SPG	3/8	10	500	-40~+100	Tube; Oil resistant Synthetic rubber Reinforcement; 3 wire braid Cover; Weather, Oil, Abrasion, Ozone and Hydrocarbon resistant synthetic rubber			
	1/2	12	470					
	5/8	16	410					
	3/4	19	375					
	1	25	327					
	1 1/4	32	240					

Туре	DN		Max. Working	Danian Tamparatura	
	[inch]	[mm]	Pressure [bar]	Design Temperature (°C)	Material of Hose
Alfagomma Flexopak 2 / Dunlop Hiflex Super Slimline 241T&241G&241X	1/4	6	420	-40~+100	
	5/16	8	375		
	3/8	10	350		Tube; Oil resistant
	1/2	12	310		Synthetic rubber
	5/8	16	280		Reinforcement; 2 wire braid
	3/4	19	240		Cover; Abrasion, Ozone and Hydrocarbon resistant synthetic rubber
	1	25	210		
	1 1/4	32	145		
	1 ½	38	125		140001
	2	51	100		
Alfagomma Flexopak 2SC HF / Dunlop Hiflex Slimline Plus 221T&221G	1/4	6	400	-40~+100	Tube;
	5/16	8	350		Oil resistant Synthetic rubber
	3/8	10	330		Reinforcement; 2 wire braid
	1/2	12	275		
	5/8	16	250		Cover; Abrasion, Ozone
	3/4	19	215		and Hydrocarbon resistant synthetic rubber
	1	25	165		

Kind of Fluid: Fuel Oil, Lubricating Oil, Hydraulic Oil, Fresh Water, Sea Water, Compressed Air, CO2

· Type approval tests carried out:

Proof Pressure Test, Burst Pressure Test, Hydraulic Impulse Test, Fire Resistance Test

· Connections:

- 1. Threaded pipe joints are to be in accordance with 12.4.2-2, Chap.12, Part D of the Rules.
- 2. Pipe flanges are to be in accordance with 12.4.3-1, Chap.12, Part D of the Rules.
- 3. Mechanical joints are to be in accordance with a standard deemed approved by the Society or to be of NK approved type.

· Production Test:

The hoses used for piping belonging to Group I & II defined by the requirements12.1.3, Chap.12, Part D of the Rules are to be subjected to hydraulic test in the presence of the Society's surveyor in accordance with the requirements 12.6.1, Chapt.12, Part D of the Rules.

· Approved manufacturers and address:

Alfagomma Hydraulic S.p.A (Castelnuovo V.-ITALY)

Via E. Mattei, 6

64020 Castelnuovo V. (TE)

Alfagomma Hydraulic S.p.A

(Figline V. ITALY)

Area Inductriale Piano Lago 87050 Figline Vegliaturo (CS)

Alfagomma Mardec Sdn. Bhd.

PLO 344, Jalan Perak 4, Pasir

Gudang Ind. Estate 81707 Johor, Malaysia Alfagomma Hydraulic UK

43 Wilcock Road

Old Boston Trading Estate Haydock

United Kingdom

Alfagomma Korea Co, Ltd.,

15, Julteo-gil, Yanggam-myeon,

Hwaseong-si, Gyeonggi-do, Korea 18630

Dunlop Hiflex AS

Vallensbaekvej 24 DK-2605 Brondby

Denmark

Dunlop Hiflex AS

Stanseveien 27

N-0903 Oslo

Norway

Dunlop Hiflex AB

Seldonsvägen 2 302 62 Halmstad

Sweden

Dunlop Hiflex Oy

Vapaalantie 8

01650 Vantaa

Finland

Dunlop Hiflex Tampere

Auto miehenkatu 31

33840 Tampere Finland Dunlop Hiflex Turku

Orikedonkatu 11

20380

Turku

Finland

· Notice:

Any significant changes in design or construction of the above items may render this certificate invalid.