



SEWERJET PLUS



// SEWER JET FOR WATER CLEANING AND HIGH-PRESSURE FLUSHING

MAIN FEATURES

- // High abrasion resistance according to EN 854:2015 – annex A
- // Low sliding resistance - higher efficiency
- // Compact, light and long lasting
- // Easy to assemble (EN ISO 1307)
- // Smooth cover (high ozone resistance)
- // High flexibility even at low temperature (-30 °C)



// SEWERJET PLUS - MINETUFF



**NEW COVER SOLUTION
FOR VERY HIGH ABRASION RESISTANCE**

Sewer hose 250 bar (3625 psi) Textile spirals

Tube: oil, detergents and hot water resistant synthetic rubber.
Reinforcement: four high tensile textile spirals.
Cover: smooth. Abrasion and ozone resistant black synthetic rubber.
Application: rubber hose for high pressure washing of sewer systems.
Safety factor: 2,5:1
Temperature: -30 °C +80 °C (-22 °F +176 °F)

Hose assembled with:

- BSP female
- BSP male

Item Code	↔			↔		↻		↻		⤴		⤵		↔	
	Dash	mm	inch	mm	inch	Mpa	psi	Mpa	psi	mm	inch	kg/m	lb/ft	m	
8M2AA020	-12	19	3/4	30,3	1,19	25	3625	62,5	9065	90	3,54	0,570	0,38	60 - 80 - 100 - 120	
8M2AA025	-16	25	1	38,8	1,53	25	3625	62,5	9065	100	3,94	0,850	0,57	60 - 80 - 100 - 120 - 150 - 160 - 180 - 200	

Length tolerance: ± 1% (norm ISO 1307)

A DEDICATED FITTING RANGE GUARANTEES HIGH SAFETY LEVEL. HOSE CAN BE SUPPLIED ASSEMBLED IN FIXED LENGTHS, PRESSURE TESTED ACCORDING TO EN 10204 3.1 B

