

TYPE APPROVAL CERTIFICATE

This is to certify:

That the Flexible Hoses of Non-Metallic Material with Permanently Fitted Couplings

with type designation(s)

Alfagomma 1SN Evolution 1SN HT150, Dunlop Hiflex Commander 150 1SN PLUS

Issued to

Alfagomma Hydraulic S.p.A.
Castelnuovo Vomano, TE, Italy

is found to comply with

DNV GL class programme DNVGL-CP-0183 – Type approval – Flexible hoses
DNV GL rules for classification – Ships Pt.4 Ch.6 Piping systems

Application :

Product(s) approved by this certificate is/are accepted for installation on all vessels classed by DNV.

Type:	Temperature range:	Max. working press.:	Sizes:
Alfagomma 1SN Evolution 1SN HT150	-40°C to +150°C (see cert.)	40 bar to 225 bar	DN06 to DN51
Dunlop Hiflex Commander 150 1SN PLUS	-40°C to + 150°C (see cert)	40 bar to 225 bar	DN06 to DN51

Issued at **Høvik** on **2021-05-19**

This Certificate is valid until **2026-05-18**.

for **DNV**

DNV local station: **Italy/Malta CMC**

Approval Engineer: **Andreas Hansen**

.....
Zeinab Sharifi
Head of Section

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

Flexible non-metallic hose assembly constructed according to EN 853 1SN and SAE 100 R1AT.

Type: 1SN Evolution HT 150 Blue Cover
 Inner tube: Oil Resistant Synthetic Rubber
 Reinforcement: One steel wire-braid
 Cover: Abrasion, Ozone and Hydrocarbon Resistant Synthetic Rubber
 Fitting: 11SMnPb30 (1.0718) EN 10277

Hose manufacturing location:

- Alfagomma Hydraulic S.p.A, Via E, Mattei, 6 – 64020 Castelnuovo Vomano (TE), Italy
- Alfagomma Hydraulic S.p.A, Area Industriale Piano Lago – 87050 Figline Vegliaturo (CS), Italy
- Alfagomma Malaysia Sdn. Bhd., PLO 344, Jalan Perak 4, Kawasan Perindustrian Pasir Gudang Johor, Malaysia

Coupling manufacturing location:

- Alfagomma Hydraulic S.p.A, Zona Industriale Piano Lago 87050 Mangone (CS), Italy

Application/Limitation

This certificate is valid for the specific assembly of hose and coupling type as specified, assembled and delivered by the holder (named as manufacturer) of this certificate.

Maximum working pressure:

Size	DN06	DN10	DN12	DN16	DN20	DN25	DN32	DN38	DN51
MAWP [bar]	225	180	160	130	105	88	63	50	40

The hose assembly covered by this certificate is suitable for use with:

- hydraulic fluids at temperatures ranging from -40°C to +150°C;
- water based fluids and compressed air at temperature ranging from -40°C to +110°C (DN≥19);
water based fluids and compressed air at temperature ranging from -40°C to +85°C (DN≤16");
- water at temperatures ranging from 0°C to +70°C.

For use with compressed air or gases the cover shall be pin pricked.

The hose covered by this certificate shall not be used in systems subject to pressure below atmospheric or vacuum.

Flexible hoses are only to be used in short lengths where it is necessary due to vibrations or flexible mounting of the machinery. The hoses shall not replace/be used where permanent piping is possible/required.

The outer end of the pipe coupling (performing the connection to the fixed piping) is not covered by this certificate and shall follow the below requirements:

- Flanged ends shall be according to a recognized standard;
- Slip-on threaded joints having pipe threads where pressure-tight joints are made on the threads with parallel or tapered threads, shall comply with requirements of a recognized standard. Limitations stated in DNVGL-RU-SHIP Pt.4 Ch.6 Sec.9 [5.2.6] to be followed;
- If these outer ends are going to be part of a mechanical joint as covered by DNVGL-RU-SHIP Pt.4 Ch.7 Sec.9 [Table 10], they shall be separately type approved.

The hose assemblies must only be fitted in places where they are always accessible.

The hose assemblies are to be mounted in accordance with the manufacturer's instructions.

Production testing

All hose assemblies delivered under the DNV type approval scheme shall be subject to a pressure test at 1.5 times the maximum working pressure and shall be delivered with the pressure test report with reference to this type approval certificate.

Type Approval documentation

Tests carried out

Dimensional check, cold flexibility, oil resistance, ozone, cover adhesion, change in length, burst test, impulse test, and fire resistance test.

Marking of product

For traceability to this Type Approval, the products are at least to be marked with:

- hose manufacturer's name or trademark;
- date of manufacture (month/year);
- designation type reference;
- nominal diameter;
- pressure rating;
- temperature rating.

Periodical assessment

For retention of the Type Approval, a DNV Surveyor shall perform periodical assessment after two years (+/- 90 days) and after 3.5 years (+/- 90 days) to verify that the conditions for the approval are complied with. Reference is made to DNVGL-CP-0338.