



## SEWERJET FLEX



## // SEWERJET FLEX

**The hose has a multi-spiral steel cord construction that makes it an highly innovative and reliable product designed to meet the ever changing market demands**

- Specifically engineered for high-pressure water jetting and sewer flushing, clearing blocked drains and culverts.
- The two high tensile steel spiral reinforcements ensure the hose has ultra-high flexibility even at low temperatures (-30 °C): bend radius is greatly reduced especially when compared to standard products currently available in the market.
- Compact and lightweight construction offers easier handling and improved jetting performance providing longer service life.
- The new smooth, extra high abrasion resistant cover is made to withstand constant dragging, offering an overall improvement in efficiency of operation.
- New SEWERJET FLEX is the ideal solution for Vacuum Trucks OEM's and operators. Utility companies and Drainage Contractors who all need a reliable, flexible and durable product for all their sewer jetting applications.



## // SEWERJET FLEX - MINETUFF



NEW COVER SOLUTION  
FOR VERY HIGH ABRASION RESISTANCE

### Sewer hose 250 bar (3625 psi)

#### Wire spirals

**Tube:** oil, detergents and hot water resistant synthetic rubber,

**Reinforcement:** two high tensile steel spirals.

**Cover:** smooth, Abrasion, ozone and very low sliding resistance black synthetic rubber.

**Application:** sewer jetting and heavy duty, high pressure water cleaning and extremely flexible.

**Safety factor:** 2,5:1

**Temperature:** -30 °C +80 °C (-22 °F +176 °F)

#### Hose assembled with:

- BSP female
- BSP male

Item Code	↻			↻		↻		↻		↻		↻		m
	Dash	mm	inch	mm	inch	Mpa	psi	Mpa	psi	mm	inch	kg/m	lb/ft	
1004973	8	13,0	1/2"	21,0	0,83	25,0	3,63	62,5	625	50	1,97	0,444	0,30	40
1004632	8	13,0	1/2"	21,0	0,83	25,0	3,63	62,5	625	50	1,97	0,444	0,30	60
1004633	8	13,0	1/2"	21,0	0,83	25,0	3,63	62,5	625	50	1,97	0,444	0,30	80
1004974	12	19,0	3/4"	27,4	1,08	25,0	3,63	62,5	625	60	2,36	0,551	0,38	40
1004635	12	19,0	3/4"	27,4	1,08	25,0	3,63	62,5	625	60	2,36	0,551	0,38	80
1004636	12	19,0	3/4"	27,4	1,08	25,0	3,63	62,5	625	60	2,36	0,551	0,38	100
1004637	12	19,0	3/4"	27,4	1,08	25,0	3,63	62,5	625	60	2,36	0,551	0,38	120
1004975	16	25,0	1"	33,7	1,33	25,0	3,63	62,5	625	80	3,15	0,990	0,67	40
1004758	16	25,0	1"	33,7	1,33	25,0	3,63	62,5	625	80	3,15	0,990	0,67	80
1004548	16	25,0	1"	33,7	1,33	25,0	3,63	62,5	625	80	3,15	0,990	0,67	100
1004549	16	25,0	1"	33,7	1,33	25,0	3,63	62,5	625	80	3,15	0,990	0,67	120
1004815	16	25,0	1"	33,7	1,33	25,0	3,63	62,5	625	80	3,15	0,990	0,67	150
1004546	16	25,0	1"	33,7	1,33	25,0	3,63	62,5	625	80	3,15	0,990	0,67	160
1004547	16	25,0	1"	33,7	1,33	25,0	3,63	62,5	625	80	3,15	0,990	0,67	180
1004538	16	25,0	1"	33,7	1,33	25,0	3,63	62,5	625	80	3,15	0,990	0,67	200
1004976	20	32,0	1 1/4"	40,8	1,61	25,0	3,63	62,5	625	120	4,72	1,200	0,81	40
1004541	20	32,0	1 1/4"	40,8	1,61	25,0	3,63	62,5	625	120	4,72	1,200	0,81	100
1004543	20	32,0	1 1/4"	40,8	1,61	25,0	3,63	62,5	625	120	4,72	1,200	0,81	120
1004797	20	32,0	1 1/4"	40,8	1,61	25,0	3,63	62,5	625	120	4,72	1,200	0,81	150
1004544	20	32,0	1 1/4"	40,8	1,61	25,0	3,63	62,5	625	120	4,72	1,200	0,81	160
1004545	20	32,0	1 1/4"	40,8	1,61	25,0	3,63	62,5	625	120	4,72	1,200	0,81	180

Length tolerance: ± 1% (norm ISO 1307)

A DEDICATED FITTINGS RANGE ENSURES HIGH SAFETY LEVEL, PRESSURE TESTED ACCORDING TO EN 10204 3,1 B





**HEADQUARTER**

**Alfagomma SpA**

Via Torri Bianche 1

20871 Vimercate (MB) Italy

[marketing@alfagomma.com](mailto:marketing@alfagomma.com)

[www.alfagomma.com](http://www.alfagomma.com)