



ALFAGOMMA

DOCK AND SHIP TO SHIP HOSE





// ALFAGOMMA DOCK AND SHIP TO SHIP RANGE

ALFAGOMMA has developed a range of dock and ship to ship hoses to meet the strict regulations and International Standards of the Oil & Gas Industry.

Over 60 years of experience in hose Research, Development and production, assure the right product for our customers needs, in any demanding environmental condition.

ALFAGOMMA has the capability to manufacture in light, medium and heavy duty constructions suitable for conveying various fluid products.

HOSE

The ALFAGOMMA dock range is especially designed to work safely in severe environmental circumstances:

- ▲ OCIMF, EN 1765 and EN 1762 international standards
- ▲ DNV-GL certificate
- ▲ Special Safe lining design
- ▲ MBR up to 4 times the ID
- ▲ Technical support for testing and maintenance
- ▲ High axial load hose resistance

BUILT-IN SAFE LINING DESIGN

This unique SAFE LINING DESIGN hose is available with built-in fittings.

These metal fittings are incorporated into the SAFE LINING construction during manufacture so as to maintain maximum holding power of the complete assembly.

The Safe Lining Design takes effect when the main lining suffers cuts, tearing or the occurrence of ageing.



// 60DAA

**Fuel-oil S&D 10 bar (150 psi) - Heavy duty
EN 1765/S10****Tube:** black NBR.**Reinforcement:** high tensile textile cords with embedded steel helix wire.**Cover:** black CR- abrasion, ozone, sea water and hydrocarbon resistant.**Application:** crude oil and liquid petroleum products suction and delivery to/from tankers and bunkering vessels.

Max 55% aromatic content resistance. Electrically continuous (discontinuous on request).

Also available: 60EAA 100% aromatic content • 60FAA biofuel.

Safety factor: 4:1**Constant operation:** -20 °C +82 °C (-4 °F +180 °F)**Diameters:** From 4" to 12"**Built-in steel nipples with fixed or swivel flanges.**

// 64AAA

**Fuel-oil delivery 10 bar (150 psi) - Heavy duty
EN 1765/L10****Tube:** black NBR.**Reinforcement:** high tensile textile cords.**Cover:** black CR- abrasion, ozone, sea water and hydrocarbon resistant.**Application:** crude oil and liquid petroleum products delivery to/from tankers and bunkering vessels. Max 55% aromatic content resistance.

Electrically continuous (discontinuous on request).

Safety factor: 4:1

Also available: 64BAA 100% aromatic content • 64CAA biofuel.

Constant operation: -20 °C +82 °C (-4 °F +180 °F)**Diameters:** From 4" to 12"**Built-in steel nipples with fixed or swivel flanges.**

// 60NAA

**Fuel-oil S&D 15 bar (225 psi)
EN 1765/S15****Tube:** black NBR.**Reinforcement:** high tensile textile cords with embedded steel helix wire.**Cover:** black CR- abrasion, ozone, sea water and hydrocarbon resistant.**Application:** crude oil and liquid petroleum products suction and delivery to/from tankers and bunkering vessels.

Max 55% aromatic content resistance. Electrically continuous (discontinuous on request).

Safety factor: 4:1**Constant operation:** -20 °C +82 °C (-4 °F +180 °F)**Diameters:** From 3" to 6"

Available with swaged fittings.

// 60GAA

**Fuel-oil S&D 15 bar (225 psi) - Heavy duty
EN 1765/S15****Tube:** black NBR.**Reinforcement:** high tensile textile cords with embedded steel helix wire.**Cover:** black CR- abrasion, ozone, sea water and hydrocarbon resistant.**Application:** crude oil and liquid petroleum products suction and delivery to/from tankers and bunkering vessels.

Max 55% aromatic content resistance. Electrically continuous (discontinuous on request).

Also available: 60HAA 100% aromatic content • 60IAA biofuel.

Safety factor: 4:1**Constant operation:** -20 °C +82 °C (-4 °F +180 °F)**Diameters:** From 4" to 12"**Built-in steel nipples with fixed or swivel flanges.**

DNVGL.COM/AF

Dimensions shown may be changed without prior notice

// 64DAA

**Fuel-oil delivery 15 bar (225 psi) - Heavy duty EN 1765/L15****Tube:** black NBR.**Reinforcement:** high tensile textile cords.**Cover:** black CR- abrasion, ozone, sea water and hydrocarbon resistant.**Application:** crude oil and liquid petroleum products delivery to/from tankers and bunkering vessels. Specially designed for STS operations.

Max 55% aromatic content resistance. Electrically continuous (discontinuous on request).

Also available: 64EAA 100% aromatic content • 64FAA biofuel.

Safety factor: 4:1**Constant operation:** -20 °C +82 °C (-4 °F +180 °F)**Diameters:** From 4" to 12"**Built-in steel nipples with fixed or swivel flanges.**

// 60JAA

**LPG S&D - 25 bar (375 psi) - Heavy duty EN 1762: 2003 Type SD / M****Tube:** black NBR.**Reinforcement:** high tensile textile cords with embedded steel helix wires.**Cover:** black CR - abrasion, ozone, salt water and hydrocarbon resistant - pin pricked.**Application:** LPG transfer in onshore and offshore applications. Also suitable for fuel and oil transfer max 55% aromatic content resistance. Electrically continuous (discontinuous on request).**Safety factor:** 4:1**Constant operation:** -30 °C +70 °C (-22 °F +158 °F)**Diameters:** From 4" to 12"**Built-in steel nipples with fixed or swivel flanges.**

// 60PAA

**Fuel-oil S&D 20 bar (300 psi) WP exceeds EN 1765/S15****Tube:** black NBR.**Reinforcement:** high tensile textile cords with embedded steel helix wire.**Cover:** black CR - abrasion, ozone, sea water and hydrocarbon resistant.**Application:** fuel and oil suction and delivery. Designed for long service life in heavy duty applications. Also suitable for bunkering service.

Electrically continuous (discontinuous on request).

Safety factor: 3:1**Constant operation:** -20 °C +82 °C (-4 °F +180 °F)**Diameters:** From 3" to 12"**Available with swaged fittings.**

// 64PAA

**Fuel-oil delivery 20 bar (300 psi) WP exceeds EN 1765/L15****Tube:** black NBR.**Reinforcement:** high tensile textile cords.**Cover:** black CR - abrasion, ozone, sea water and hydrocarbon resistant.**Application:** fuel and oil delivery. Designed for long service life in heavy duty applications. Also suitable for bunkering service.

Electrically continuous (discontinuous on request).

Safety factor: 3:1**Constant operation:** -20 °C +82 °C (-4 °F +180 °F)**Diameters:** From 3" to 8"**Available with swaged fittings.**

// 6N511 EN

**Fuel - Oil S&D - heavy duty
EN 13765 - arrêté TMD****Inner wire:** Galvanised steel wire**Tube:** Polypropylene film**Cover:** Blue PVC coated fabric with longitudinal yellow stripe**Outer wire:** Galvanised steel wire**Use:** Fuel and Oil suction and delivery to/from tankers and bunkering vessels**Safety factor:** 5:1**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)**Electrical Conductivity:** Ensured by the 2 wires in contact with fittings**Electrical Resistance:** ≤ 2.5 Ohm/mt up to DN 50mm (2");
≤ 1 Ohm/mt over DN 50mm (2")**Diameters:** From 6" to 12"**Available connection:**

- Male BSPP
- Male NPT
- Fixed and Swivel Flange

// 5N551 EN

**Acid-Chemical S&D - heavy duty
EN 13765 - arrêté TMD****Inner wire:** Polypropylene coated steel wire**Tube:** Polypropylene film**Cover:** Black PVC coated fabric with longitudinal white stripe**Outer wire:** Galvanised steel wire**Use:** Acid and Chemical suction and delivery to/from tankers and bunkering vessels**Safety factor:** 5:1**Constant operation:** -30 °C +80 °C (-22 °F +176 °F)**Electrical Conductivity:** Ensured by the 2 wires in contact with fittings**Electrical Resistance:** ≤ 2.5 Ohm/mt up to DN 50mm (2");
≤ 1 Ohm/mt over DN 50mm (2")**Diameters:** From 6" to 10"**Available connection:**

- Male BSPP
- Male NPT
- Fixed and Swivel Flange

// 5N331 EN

**Acid-Chemical S&D - heavy duty - PTFE
EN 13765 - arrêté TMD****Inner wire:** Stainless Steel 316 wire**Tube:** PTFE film**Cover:** Red PVC coated fabric with longitudinal white stripe**Outer wire:** Galvanised steel wire**Use:** Acid and Chemical suction and delivery to/from tankers and bunkering vessels**Safety factor:** 5:1**Constant operation:** -30 °C +100 °C (-22 °F +212 °F)**Electrical Conductivity:** Ensured by the 2 wires in contact with fittings**Electrical Resistance:** ≤ 2.5 Ohm/mt up to DN 50mm (2");
≤ 1 Ohm/mt over DN 50mm (2")**Diameters:** From 6" to 12"**Available connection:**


- Male BSPP
- Male NPT
- Fixed and Swivel Flange

Dimensions shown may be changed without prior notice

// BUILT-IN FITTINGS

Built-in fittings are available with welding neck, slip on and swivel flanges.
Nipple material selected according to international standards and customer request.

- ▲ Plated Carbon Steel
- ▲ Low Temperature Steel
- ▲ Stainless Steel



// FIXED AND SWIVEL FLANGES

Flanges are available in the most common materials according to International standards and suitable for dock and offshore applications:

- ▲ ASTM A105
- ▲ ASTM A350 GR. LF2
- ▲ ASTM A182 GR. F316

	FIXED		SWIVEL		
Welding Neck			Lap Joint		
Slip-on					

ALFAGOMMA offers a complete range of flange faces for built-in and swaged fittings:

- ▲ Flat Face (FF)
- ▲ Raised Face (RF)
- ▲ Ring Type Joint (RTJ)

THE ALFAGOMMA GROUP

ALFAGOMMA

ARGENTINA – Buenos Aires
Moreno Store Center
Belisario Roldán 2616 - CP. 1744
La Reja - Bs. As.
+54 (11) 5365-6062/6063

AUSTRALIA – Sydney
50 Honeycomb Drive
Eastern Creek
Sydney, NSW 2766
+61 (2) 98 53 09 00
sydney@alfagomma.com.au

BELGIUM & NETHERLANDS – Benelux
Koeweideblock 4/D3
1785 Merchtem
+32 (0)52 509 747
info.benelux@alfagomma.com

BRAZIL – Guaranésia
Rua Felice Gennasio 401
Distrito Indl. Dr. Firmino Rocha de Freitas
37810-000 - Guaranésia, MG - Brasil
+55 (35) 35 55 0408
contato@alfagomma.com.br

CANADA – Montreal
6550 Abrams
St. Laurent, Montreal
Quebec H4S 1Y2
+1 (514) 33 35 577
info@alfagomma.ca

CHINA – Ningbo
No. 1 Cidong South Avenue
Coastal Economic Development Zone
Cixi, Zhejiang, China 315311
+86 (574) 88 15 72 88
alfagomma.china@alfagomma.com.cn

FRANCE – Villepinte
Le Sisley – Parc d'activité Paris Nord 2
23 Allée des Impressionnistes
93420 Villepinte
+33 (1) 48172121
agfrance.info@alfagomma.com

GERMANY – Herne
Friedrich der Grosse 10
44628 Herne
+49 (2323) 14 730
info.germany@alfagomma.com

GREECE – Athens
85 Kifissou Avenue
12241 Aigaleo, Athens
+30 (210) 41 19 909
info.hellas@alfagomma.com

INDONESIA – Tigaraksa
JL. Raya Pemda Tigaraksa km. 4
No 34, Matagara
Tigaraksa, Tangerang 15720
+62 (21) 59 96 301
jakarta@alfagomma.co.id

ITALY – Vimercate
Via Torri Bianche 1
20871 Vimercate (MB)
+39 (039) 60 161
info@alfagomma.com

MALAYSIA – Pasir Gudang
Plo 405, Jalan Perak 4
81707 Pasir Gudang
Negeri Johor Darul Takzim
+60 (7) 25 72 000
alfagomma@alfagomma.com.my

MEXICO – Torreón
Av. Industria de la transformacion
Parque Pymes 585
27400 Torreón, Coahuila
+52 8713125026
alfagomma.mexico@alfagomma.com

SINGAPORE
14 Tuas Ave 11
Singapore 639080
+65 6360 9000
alfagomma@alfagomma.com.sg

SOUTH AFRICA – Johannesburg
17 Quark Crescent Linbro Business Park
Sandton 2065
+27 (11) 20 10 900
alfagomma@alfagomma.co.za

SOUTH KOREA – Hwasung
15 Julteo Gil
Yangkam-Myun, Hwasung-Si
Kyungki-Do 18630
+82 (31) 35 28 671
alfagomma@alfagomma.co.kr

THAILAND – Bangkok
60/21 Moo.4 King Kaew Road
Racha Thewa SubDistrict, Bang Phli District
Samut Prakan Province, 10540
+66 (0) 2 136 2388
sales@alfagomma.co.th

UNITED KINGDOM – Haydock
43 Wilcock Road
Old Boston Trading Estate Haydock
St. Helens WA11 9TG
+44 (1942) 40 76 80
haydock.sales@alfagomma.com

UNITED STATES OF AMERICA – Burlington
3520 West Avenue
IA 52601 Burlington
+1 (319) 75 89 224
info@alfagomma.us

DUNLOPHIFLEX

DENMARK – KOLDING
Kokholm 5
6000 Kolding
+45 (43) 25 40 00
kundeservice@dunlophiflex.dk

ESTONIA – Tallin
Läike tee 32/1 - Peetri alevik,
Rae vald - 75312 Harjumaa (Tallinn)
Tel: +372 (0) 605 4900
tallinn@dunlophiflex.ee

FINLAND – Pirkkala
Jasperintie 320
33960 Pirkkala
+358 (207) 625 700
info@dunlophiflex.fi

NETHERLANDS – Deventer
Hunneperkade 86
7418 BT Deventer
+31 (570) 66 05 70
info@dunlophiflex.nl

NORWAY – Kjeller
Jogstadveien 39
Pb. 7, 2027 Kjeller
2007 Kjeller
+47 (23) 00 47 00
sales@dunlophiflex.no

SWEDEN – Halmstad
Kistinge Industriområde
Seldonsvagen 2
30180 Halmstad
+46 (104) 14 44 04
halmstad@dunlophiflex.se

ARGUS

GERMANY – Ettlingen
Pforzheimer Str. 126
76275 Ettlingen
+49 (7243) 50 550
info@argus-fluidtechnik.de

UNITED KINGDOM – Salisbury
Telford Road
Salisbury, Wiltshire SP2 7PH
+44 (1722) 42 05 90
sales@hiflex-europe.com



HEADQUARTER
Alfagomma SpA
Via Torri Bianche 1
20871 Vimercate (MB) Italy
marketing@alfagomma.com
www.alfagomma.com