

TYPE APPROVAL CERTIFICATE

Certificate no.:
TAP000002W
Revision No:
5

This is to certify:

that the **Flexible Hoses of Non-Metallic Material with Permanently Fitted Couplings**

with type designation(s)

Flexor 1SN/1AT-HF (Dunlop Hiflex: Greenline plus 122), Flexor 2SN/2AT-HF (Dunlop Hiflex: Greenline plus 222), 1SN MINETUFF (Dunlop Hiflex: 1SN HI-TUFF), 2SN MINETUFF (Dunlop Hiflex: 2SN HI-TUFF)

issued to

Alfagomma Hydraulic S.p.A.
Castelnuovo Vomano – Castellalto, TE, Italy

is found to comply with

DNV rules for classification – Ships Pt.4 Ch.6 Piping systems
DNV-OS-D101 – Marine and machinery systems and equipment, Edition July 2021
DNV class programme DNV-CP-0183 – Type approval – Flexible non-metallic hoses

Application:

Product(s) approved by this certificate is/are accepted for installation on vessels classed by DNV.

Type:	Temperature range:	Max. working press.:	Sizes:
Flexor 1SN/1AT-HF (Dunlop Hiflex: Greenline plus 122)	-40°C to +100°C	40 bar to 225 bar	DN6 to DN51
Flexor 2SN/2AT-HF (Dunlop Hiflex: Greenline plus 222)	-40°C to +100°C	80 bar to 400 bar	DN6 to DN51
1SN MINETUFF (Dunlop Hiflex: 1SN HI-TUFF)	-40°C to +100°C	40 bar to 225 bar	DN31 to DN51
2SN MINETUFF (Dunlop Hiflex: 2SN HI-TUFF)	-40°C to +100°C	80 bar to 400 bar	DN6 to DN51

Issued at **Høvik** on **2024-09-10**

This Certificate is valid until **2029-06-29**.

for **DNV**

DNV local unit: **Italy/Malta CMC**

Approval Engineer: **Sarah Miller**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to USD 300 000.



Product description

Four types of hose assemblies. Hoses and fittings are manufactured by ALFAGOMMA Hydraulic SPA.

Hoses:

- Flexor 1SN/1AT-HF (Dunlop Hiflex: Greenline Plus 122) & 1SN MINETUFF (Dunlop Hiflex: 1SN HI-TUFF),
 Designed according to EN853 / 1SN
 Tube: Oil Resistant synthetic rubber
 Reinforcement: One high tensile steel braid (1B)
 Cover: Abrasion, Ozone and hydrocarbon resistant synthetic rubber
- Flexor 2SN/2AT-HF (Dunlop Hiflex: Greenline Plus 222) & 2SN MINETUFF (Dunlop Hiflex: 2SN HI-TUFF),
 Designed according to EN853 / 2SN
 Tube: Oil Resistant synthetic rubber
 Reinforcement: Two high tensile steel braids (2B)
 Cover: Abrasion, Ozone and hydrocarbon resistant synthetic rubber

Couplings:

- Flexor 1SN/1AT-HF & 1SN MINETUFF (Dunlop Hiflex: Greenline Plus 122 & 1SN HI-TUFF)

Nominal size (DN / inch)		Carbon Steel 11SMnPb30 Stainless Steel AISI 316			
		Skive fittings 1SN/1AT-HF		No Skive fittings 1SN/1AT-HF	AG Branding*
		AG Branding	DH Branding	DH Branding	
6	¼	-	-	D110000-04/0	H1200AD1-04
8	5/16	-	-	D110000-05/0	H1200AD1-05
10	3/8	-	-	D110000-06/0	H1200AD1-06
12	½	-	-	D110000-08/0	H1200AD1-08
16	5/8	-	-	D110000-10/0	H1200AD1-10
19	¾	-	-	D110000-12/0	H1200AD1-12
25	1	-	-	D110000-16/0	H1200AD1-16
31	1 ¼	H1100104-20	H1100104-20	D110000-20/0	H1200AD1-20
38	1 ½	H1100104-24	H1100104-24	D110000-24/0	H1200AD1-24
51	2	H1100104-32	H1100104-32	D110000-32/0	H1200AD1-32

- Flexor 2SN/2AT-HF & 2SN MINETUFF (Dunlop Hiflex: Greenline Plus 222 & 2SN HI-TUFF)

Nominal size (DN / inch)		Carbon Steel 11SMnPb30 Stainless Steel AISI 316		
		Skive fittings	No Skive fittings	AG Branding*
		AG Branding	DH Branding	
6	¼	H1100404-04 H3100404-04	D220000-04/0	H1200AD2-04
8	5/16	H1100404-05 H3100404-05	D220000-05/0	H1200AD2-05
10	3/8	H1100404-06 H3100404-06	D220000-06/0	H1200AD2-06
12	½	H1100404-08 H3100404-08	D220000-08/0	H1200AD2-08
16	5/8	H1100404-10 H3100404-10	D220000-10/0	H1200AD2-10
19	¾	H1100404-12 H3100404-12	D220000-12/0	H1200AD2-12
25	1	H1100404-16 H3100404-16	D220000-16/0	H1200AD2-16
31	1 ¼	H1100404-20 H3100404-20	D220000-20/0	H1200AD2-20
38	1 ½	H1100404-24 H3100404-24	D220000-24/0	H1200AD2-24
51	2	H1100404-32 H3100404-32	D220000-32/0	H1200AD2-32

*) AD1 and AD2 coupling are the Alfagomma branding of D11 and D22 coupling branding Dunlop Hiflex

- Flexor 2SN/2AT-HF (Dunlop Hiflex: Greenline Plus 222)

Nominal size (DN / inch)	Stainless Steel AISI 316

		AG Branding
6	¼	H3200AD2-04
8	5/16	H3200AD2-05
10	3/8	H3200AD2-06
12	½	H3200AD2-08
16	5/8	H3200AD2-10
19	¾	H3200AD2-12
25	1	H3200AD2-16
31	1 ¼	H3200AD2-20
38	1 ½	H3200AD2-24
51	2	H3200AD2-32

Application/Limitation

This certificate is valid for the specific assembly of hose and coupling type as specified, assembled and delivered by the holder (named as manufacturer) of this certificate or below assembling locations:

- 1) Alfagomma Hydraulic S.P.A., Mangone, Italy
 - 2) Dunlop Hiflex AB, Halmstad, Sweden
 - 3) Dunlop Hiflex OY, Turku, Finland
 - 4) Alfagomma hydraulic S.P.A, Bellusco, Italy
 - 5) Alfagomma Germany GmbH, Herne, Germany
 - 6) Dunlop Hiflex AS, Stavanger, Norway
 - 7) Dunlop Hiflex AS, Bergen, Norway
 - 8) Dunlop Hiflex AS, Kristiansand, Norway
 - 9) Dunlop Hiflex AS, Kolding, Denmark
 - 10) Alfagomma UK Ltd, Hydock, UK
 - 11) Alfagomma Korea Co, Ltd., Hwaseong-Si, Gyeonggi-do, Korea
 - 12) Alfagomma (Ningbo) Co. Ltd, Zhejiang, China
 - 13) Argus Fluidtechnik GmbH, Ettlingen, Germany
 - 14) Dulop Hiflex OY,PIRKKALA, Finland
- *Excluding 2SC
 *Except 1SN/2SN MINETUFF
 *Just 1SN/2SN MINETUFF

Hose assemblies are approved to use with:

- Petroleum based hydraulic fluids at temperatures ranging from -40 °C + 100 °C;
- Water based fluids at temperatures ranging from -40 °C to +70 °C;
- Water and Air at temperatures ranging from 0 °C to +70 °C.
- Fuel Oil
- CO2 systems at temperatures ranging from -60°C to 100°C (Just hose assemblies 1SN MINETUFF (Dunlop Hiflex:1SN H1-TUFF) with AD1 couplings (or D11 Dunlop Hiflex branding) up to size 1" can be used in CO2 applications)

Maximum working pressure of each hose assemblies shall be as follows:

Nominal size (DN / inch)		1SN/1AT HF 1SN MINETUFF	2SN/2AT HF 2SN MINETUFF
6	¼	225 bar	400 bar
8	5/16	215 bar	350 bar
10	3/8	180 bar	330 bar
12	½	160 bar	275 bar
16	5/8	130 bar	250 bar
19	¾	105 bar	215 bar
25	1	88 bar	165 bar
31	1 ¼	63 bar	125 bar
38	1 ½	50 bar	90 bar
51	2	40 bar	80 bar

Flexible hoses are only to be used in short lengths where it is necessary due to vibrations or flexible mounting of the machinery. The hoses shall not replace/be used where permanent piping is possible/required.

The hose assemblies must only be fitted in places where they are always accessible. Flexible hoses of these types are not to be used on boiler fronts.

The hoses are to be mounted in accordance with the manufacturer's instructions.

Hose assemblies covered by this certificate shall not be used in system subject to pressure below atmospheric or vacuum condition.

The Flexor 2SN/2AT-HF (Dunlop Hiflex: Greenline Plus 222) type with coupling H3200AD2 shall not be used in systems subject to pressure pulsation.

The cover of hoses for gaseous applications shall be pin-pricked.

Production testing

All hose assemblies delivered under the DNV type approval scheme shall be subject to a pressure test at 1.5 times the maximum working pressure and shall be delivered with the pressure test report with reference to this type approval certificate.

Type Approval documentation

Tests carried out

Change in length, dimensional check, abrasion resistance, cover adhesion test, oil resistance test, cold flexibility test, ozone resistance, fire test, burst pressure, impulse test.

Marking of product

For traceability to this Type Approval, the products are at least to be marked with:

- hose manufacturer's name or trademark;
- date of manufacture (month/year);
- designation type reference;
- nominal diameter;
- pressure rating;
- temperature rating.

Periodical assessment

This certificate is only valid if required periodical assessments are carried out with satisfactory results.

For retention of the Type Approval, a DNV Surveyor shall perform periodical assessment after two years (+/- 90 days) and after 3.5 years (+/- 90 days) to verify that the conditions for the approval are complied with. Reference is made to DNV-CP-0338.

To check the validity of this certificate, please look it up in [Search | Approval finder \(dnv.com\)](#) .