



TYPE APPROVAL CERTIFICATE

Certificate no.:
TAP00000Y9
Revision No:
7

This is to certify:

that the **Flexible Hoses of Non-Metallic Material with Permanently Fitted Couplings**

with type designation(s)
Alfabiotech 4000, 5000, 6000 (Supertuff) / Powerflexbio 4000, 5000, 6000 (TUFLEX)

issued to

Alfagomma Hydraulic S.p.A.
Castelnuovo Vomano – Castellalto, TE, Italy

is found to comply with

DNV rules for classification – Ships Pt.4 Ch.6 Piping systems
DNV-OS-D101 – Marine and machinery systems and equipment, Edition July 2021
DNV class programme DNV-CP-0183 – Type approval – Flexible non-metallic hoses

Application:

Product(s) approved by this certificate is/are accepted for installation on vessels classed by DNV.

Temperature range: -40°C to +121°C
Max. working press.: 210, 280/290, 350, 380, 420/445/450 bar
Sizes: -4 to -48 (see page 2 and page 3)

Issued at **Høvik** on **2024-05-21**

This Certificate is valid until **2024-12-31**.

for **DNV**

DNV local unit: **Italy/Malta CMC**

Approval Engineer: **Sarah Miller**

This Certificate is subject to terms and conditions overleaf. Any significant change in design or construction may render this Certificate invalid. The validity date relates to the Type Approval Certificate and not to the approval of equipment/systems installed.

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.



Product description

Five types of flexible rubber hoses with permanently attached couplings constructed according to ISO 18752 with type designations (except Alfabiotech 5000 DN76 which is not according to ISO18752)

ALFAGOMMA designations : ALFABIOTECH 4000, 5000, 6000 (SUPERTUFF)
 DUNLOP HIFLEX designations : POWERFLEXBIO 4000, 5000, 6000 (TUFLEX)

Design:

Tube : Oil resistant synthetic rubber and biodegradable hydraulic fluids
 Cover : Abrasion, ozone and hydrocarbon resistant synthetic rubber. MSHA.
 Reinforcement :
 Type 4000 : Four high tensile steel spirals
 Type 5000 : Four/six high tensile steel spirals
 Type 6000 : Four/six high tensile steel spirals

ALFABIOTECH 4000	Size		Ferrule	Insert	Ferrule	Insert
	3/4"	-12	H1200204-12	H12xxxxx-12	-	-
	1"	-16	H1200204-16	H12xxxxx-16	H1100404-16 H3100404-16	H12xxxxx-16 H32xxxxx-16
	1 1/4"	-20	H1200204-20	H12xxxxx-20	-	-
	1 1/2"	-24	H1300NS4-24	H13xxxxx-24	H1400200-24	H14xxxxx-24
2"	-32	H1300NS4-32	H13xxxxx-32	H1400200-32	H14xxxxx-32	

ALFABIOTECH 5000							
Size		Ferrule	Insert	Ferrule	Insert	Ferrule	Insert
5/8"	-10	-	-	H1100404-10	H12xxxxx-10	-	-
3/4"	-12	H1300NS4-12	H13xxxxx-12	H1100404-12	H12xxxxx-12	H1400200-12	H14xxxxx-12
1"	-16	H1300NS4-16	H13xxxxx-16	H1100404-16	H12xxxxx-16	H1400200-16	H14xxxxx-16
1 1/4"	-20	H1300NS4-20	H13xxxxx-20	-	-	H1400200-20	H14xxxxx-20
1 1/2"	-24	H1300NS6-24	H13xxxxx-24	-	-	H1400301-24 H3400301-24	H14xxxxx-24 H34xxxxx-24
2"	-32	H1300NS6-32	H13xxxxx-32	-	-	H1400301-32	H14xxxxx-32
2 1/2"	-40	-	-	-	-	H1T00600-40	H1Txxxxx-40
3"	-48	-	-	-	-	H1T00600-48 H3T00600-48	H1Txxxxx-48 H3Txxxxx-48

ALFABIOTECH 6000					
Size		Ferrule	Insert	Ferrule	Insert
1/4"	-04	H1100404-04 H3100404-04	H12xxxxx-04 H32xxxxx-04		
3/8"	-06	H1100404-06 H3100404-06	H12xxxxx-06 H32xxxxx-06		
1/2"	-08	H1100404-08 H3100404-08	H12xxxxx-08 H32xxxxx-08	H1400200-08	H14xxxxx-08
5/8"	-10	-	-	H1400301-10 H3400301-10	H14xxxxx-10 H34xxxxx-10
3/4"	-12	H1300NS4-12	H13xxxxx-12	H1400200-12 H3400200-12	H14xxxxx-12 H34xxxxx-12
1"	-16	H1300NS4-16	H13xxxxx-16	H1400200-16 H3400200-16	H14xxxxx-16 H34xxxxx-16
1 1/4"	-20	H1300NS6-20	H13xxxxx-20	H1400301-20 H3400301-20	H14xxxxx-20 H34xxxxx-20
1 1/2"	-24	-	-	H1400301-24 H3400301-24	H14xxxxx-24 H34xxxxx-24
2"	-32	-	-	H1T00600-32 H3T00600-32	H1Txxxxx-32 H3Txxxxx-32

End fittings material : Carbon Steel 11SMnPb30 according UNI EN 10277
 INOX Steel AISI 316

Manufacturing plants:

Hoses : Alfagomma Hydraulic S.p.A., Via Enrico Mattei no.6, 64020 - Castelnuovo Vomano (TE)
 Couplings : Alfagomma Hydraulic S.p.A., Area Industriale Piano Lago, 87050 Mangone (CS) – Italy

Application/Limitation

This certificate is valid for the specific assembly of hose and coupling type as specified, assembled and delivered by the holder (named as manufacturer) of this certificate or below assembling locations:

- 1) Dunlop Hiflex AB, Halmstad, Sweden
- 2) Dunlop Hiflex AS, Stavanger, Norway
- 3) Dunlop Hiflex AS, Kristiansand, Norway

Hose assemblies covered by this certificate may be used in:

Petroleum based (-40°C to +121°C), water based Hydraulic fluids (-40°C to +70°C) fluids, water and air (0°C to +70°C)

Maximum working pressure for each type and size of hose assembly shall be as below:

Size			ABT 4K	ABT 5K	ABT 6K
DN6	-04	1/4"	-	-	450 bar
DN10	-06	3/8"	-	-	445 bar
DN12	-08	1/2"	-	-	420 bar
DN16	-10	5/8"	-	350 bar	420 bar
DN19	-12	3/4"	280 bar	350 bar	420 bar
DN25	-16	1"	280 bar	350 bar	420 bar
DN31	-20	1 1/4"	280 bar	350 bar	420 bar
DN38	-24	1 1/2"	290 bar	350 bar	420 bar
DN51	-32	2"	280 bar	350 bar	420 bar
DN63	-40	2 1/2"	-	350 bar	-
DN76	-48	3"	-	350 bar	-

Flexible hoses are only to be used in short lengths where it is necessary due to vibrations or flexible mounting of the machinery. The hoses shall not replace/be used where permanent piping is possible/required.

The hose assemblies must only be fitted in places where they are always accessible. Flexible hoses of these types are not to be used on boiler fronts.

Hose assemblies covered by this certificate shall not be used in system subject to pressure below atmospheric or vacuum condition.

The cover of hoses for gaseous applications shall be pin pricked.

Production testing

All hose assemblies delivered under the DNV type approval scheme shall be subject to a pressure test at 1.5 times the maximum working pressure and shall be delivered with the pressure test report with reference to this type approval certificate.

Type Approval documentation

Tests carried out

Dimensional check, change in length, burst pressure, proof pressure, impulse test, oil resistance test, ozone resistance test, cold flexibility test, cover adhesion test, fire test

Marking of product

For traceability to this Type Approval, the products are at least to be marked with:

- hose manufacturer's name or trademark;
- date of manufacture (month/year);
- designation type reference;



Job ID: **262.1-016580-14**
Certificate no.: **TAP00000Y9**
Revision No: **7**

- nominal diameter;
- pressure rating;
- temperature rating.

Periodical assessment

For retention of the Type Approval, a DNV Surveyor shall perform periodical assessment after two years (+/- 90 days) and after 3.5 years (+/- 90 days) to verify that the conditions for the approval are complied with. Reference is made to DNV-CP-0338.